



# TG5120 DYNAMIC 5

When a task demands comfort and high levels of protection, this is the glove for you. Close fit comfort along with cut level 5 protection from a 13-gauge blend of nylon and HPPE. The unique Cohesion Crystal palm coating offers resistance to 'tack' build up from hot metal adhesives. Ideal for use in dry, cold and hot conditions and has excellent thermal conductivity resistance.



**COHESION CRYSTAL**

## Key Features

- Cohesion Crystal palm coating
- Nylon, HPPE and glass shell
- Resists 'tack' build up from hot metal adhesives

## Ideal for

- Glass and window handling
- Hot melt adhesive and sealant work
- Windshield replacement
- Manufacturing



## SPECIFICATIONS

<b>Code:</b>	TG5120	<b>EN 388:</b>	4542
<b>Name:</b>	DYNAMIC 5	<b>Sizes:</b>	XS-2XL
<b>Length:</b>	220-270mm	<b>Coating:</b>	Cohesion Crystal
<b>Liner:</b>	Nylon/HPPE/Glass	<b>Gauge:</b>	13-gauge
<b>Bag:</b>	10	<b>Case:</b>	100

### MAINTENANCE

Gloves should be frequently inspected for excessive wear. Laundering could affect the cut resistance of the glove.

### DISPOSAL

Worn gloves should be disposed of in the proper containers.

### STORAGE

Gloves should be stored in original packaging away from excessive heat and wet conditions.

