



Dry



Wet



Heat



Oily



Cold



Chemical



NGT1290

The UK's first 21 gauge EN388:2016 cut level A safety glove, ultra-lightweight close fitting and flexible with a high tech Polyurethane Dispersion (PUD) – water-based coating that provides excellent grip in dry conditions. Fully touchscreen compatible.

Key Features

- UK's first 21 gauge EN388:2016 cut level A safety glove
- Super lightweight
- Highly tactile, touchscreen compatible
- Innovative PUD coating, providing high levels of grip
- High performance liner, dirt & abrasion resistant

Ideal for

- Automotive
- Fine product assembly work
- Machinery and equipment
- Metal fabrication
- Tasks which require use of touchscreen

Sizes:	6-11	Gauge:	21gg
Liner:	Nylon	Coating:	PUD
No/Bag:	10	No/Carton:	200



NGT1290

Glove Specifications

Glove lengths

220mm-270mm

Glove Weight

21 gauge

Liner Type

Nylon

Glove colour

Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour

Black

Dip type

PUD

Dip Application

Palm Dipped

Glove Treatment

X-Dura



Packaging Information

Qty/bag

10 pairs

Qty/carton

200 pairs

Carton Dimensions

300mm x 600mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.