



Dry



Wet



Heat



Oily



Cold



Chemical



TG1050

A lightweight, X-Dura Latex palm coated handling glove suitable in wet and dry conditions. High stretch liner delivers an outstanding wearer experience.

Key Features

- Rugged and durable grip
- High tear resistance
- Flexible and very comfortable
- Excellent dexterity, highly tactile

Ideal for

- Construction
- Waste and recycling
- Warehousing
- Automotive
- Rail
- Construction and Utility
- Engineering and Manufacturing
- Oil and Gas

| | | | |
|----------------|-------|-------------------|--------------|
| Sizes: | 6-11 | Gauge: | 15gg |
| Liner: | Nylon | Coating: | X-Dura Latex |
| No/Bag: | 10 | No/Carton: | 200 |

TG1050

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
15 gauge

Liner Type
Nylon

Glove colour
Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

Overlock Colours

| SIZE | XS-6 | S-7 | M-8 | L-9 | XL-10 | 2XL-11 | 3XL-12 |
|--------|------|-----|--------|-------|--------|--------|--------|
| COLOUR | BLUE | RED | ORANGE | WHITE | YELLOW | BLACK | GREEN |

Coating Specifications

Coating colour
Black

Dip type
Crinkle Latex

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
200 pairs

Carton Dimensions
400mm x 520mm x 450mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.