

EN 407:2004



X 1 X X X X



Dry



Wet



Heat



Oily



Cold



Chemical



TG5120

A close-fitting Cut C / A3 glove featuring the unique Cohesion Crystal palm coating developed to protect against hot melt/tack build up.

Highly durable and tear resistant and offers superb grip in dry conditions.

Key Features

- EN407
- Highly durable and tear resistant
- Transparent cohesion crystal coating developed for hot melt application
- Excellent grip in dry condition

Ideal for

- Window and door fabrication
- Manufacturing
- Hot melt and sealant work
- Risk of tack build up and cross contamination

Sizes:	6-11	Gauge:	13gg
Liner:	Polyamide/PPE/ Glass/Elastane	Coating:	Liquid Silicone Rubber
No/Bag:	10	No/Carton:	100

TG5120

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
13 gauge

Liner Type
Polyamide/HPPE/Glass fibre/Elastane

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Clear

Dip type
Liquid Silicone Rubber

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 500mm x 400mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.