



Dry



Wet



Heat



Oily



Cold



Chemical



TG365

A flexible, close fitting palm dipped X-Dura nitrile foam glove with high abrasion and tear resistance. Cut level B protection and excellent gripping power for wet and dry surfaces.

Key Features

- Fine gauge liner with generous knit wrist for secure and comfortable fit
- Highly durable and tear resistant
- Nitrile foam coating provides good grip in wet, dry and oily conditions

Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Oil and Gas
- Waste, Recycling and Local Authority

Sizes:	6-11	Gauge:	13gg
Liner:	Polyamide/HPPE/ Glass fibre	Coating:	X-Dura Nitrile
No/Bag:	10	No/Carton:	200



TG365

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
13 gauge

Liner Type
Polyamide/HPPE/Glass fibre

Glove colour
Pantone 158c / R:245 G:127 B:498 / C:2 M:63 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
Polyurethane

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
200 pairs

Carton Dimensions
400mm x 520mm x 450mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.