

EN 407:2004



4 1 3 2 X X



Dry



Wet



Heat



Oily



Cold



Chemical



TG5130

A close fitting mono-filament Aramid cut level D glove featuring the unique Cohesion Carbon palm coating offering outstanding hot contact heat and oil resistance.

Key Features

- Heat resistant mono-filament Aramid liner
- Cohesion carbon coating offers a highly durable and resilient barrier
- Excellent grip
- Reinforced thumb crotch for improved durability and longevity

Ideal for

- Hot surface contact
- Risk of oil and chemical contamination
- Automotive
- General metalwork and fabrication
- Waste and recycling
- Heavy manufacturing

Sizes:	6-11	Gauge:	13gg
Liner:	Nylon/Aramid/Steel	Coating:	Cohesion Carbon
No/Bag:	10	No/Carton:	100

TG5130

Glove Specifications

Glove lengths
220mm-260mm

Glove Weight
13 gauge

Liner Type
Nylon/Aramid/Steel

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Cohesion Carbon

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 450mm x 300mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.